

DEFY 3

It's a new year, and an all-new Defy. Race-inspired engineering with an all-new tubeset from the world leader in aluminum technology. Defy is lighter to help with the climbs, stiffer to maximize power transfer and just plain faster than its closest competitor.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Blue/Silver/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
COMPONENTS	SHOCK	N / A
	HANDLEBAR	Giant Alloy Anatomic Bend, 26.0
	STEM	Giant Alloy 4-bolt
	SEATPOST	Giant Alloy, 30.9
DRIVETRAIN	SADDLE	Giant Performance Road, Men's
	PEDALS	Caged w/ Clips
	SHIFTERS	Shimano 2200
	FRONT DERAILLEUR	Shimano 2203
WHEELS	REAR DERAILLEUR	Shimano Sora
	BRAKES	Tektro R350 Dual Pivot
	BRAKE LEVERS	Shimano 2200, short reach
	CASSETTE	SRAM PG 850 11/26, 8-speed
EXTRAS	CHAIN	KMC Z7
	CRANKSET	FSA Vero, 30/42/52
	BOTTOM BRACKET	Cartridge
	RIMS	Alex DA-22, Double Wall
	HUBS	Formula 32H
	SPOKES	Stainless
	TIRES	Kenda Kriterium, 700x25

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Ride like a pro on the most advanced ALUXX SL aluminum frame yet. Giant flexes some engineering muscle to produce a lighter, stiffer tubeset than before, with better ride tuning, so you get the best of everything.



FEATURES

- 8-speed Shimano shifting with Sora rear derailleur
- Composite fork with OverDrive steerer
- Alex rims, Formula hubs/stainless spokes wheelset with Kenda Kriterium Tires

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	382552	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5 cm	382553	72.0	74.0	53.0	14.5	42.0	99.0	29.7
M/50.0 cm	382554	72.5	73.0	54.5	16.5	42.0	99.0	30.6
M/L/53.5 cm	382555	72.5	73.0	56.0	18.5	42.0	100.5	31.1
L/55.5 cm	382556	72.5	72.0	57.5	20.5	42.0	100.8	32.0
XL/58.5 cm	382557	72.5	72.0	59.5	22.5	42.0	102.8	32.8

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire